
PROVEN TO REDUCE YOUR COOLANT WASTE UP TO 90%

The Effective Solution to Coolant Management Problems

PRAB's Guardian Coolant Recycling System is a centralized, economical solution to the high costs associated with maintaining water-based coolants and washwater in the metalworking industry. The Guardian system recycles used coolants, reducing waste fluids by up to 90%, and eliminates concerns about wastewater haul-away liabilities. Everything you need for centralized coolant recycling is included with the Guardian. Each turnkey system is designed for easy installation, quick start-up, and simple, efficient operation. PRAB backs every Guardian system with a 100% performance guarantee.



Documented Results Achieved by PRAB Customers:

- Reduced new fluid purchases up to 75%
- Decreased fluid disposal costs by approximately 90%
- Extended tool life by up to 25%
- Reduced machine downtime by an average of 50%
- Improved surface finish by an average of 25%

Guardian Coolant Recycling System

System Features:

- Processes up to 1,500 gallons of coolant per hour with standard configurations; larger capacity is available upon request
- Removes tramp oils and reduces up to 75% of new fluid purchases
- Reduces hazardous waste disposal costs up to 90%
- Typically generates system payback in 6-9 months
- Minimizes operator involvement and training


- Achieves tighter coolant clarity tolerances with optional polishing filter
- Extends tool life and saves up to 25% in new tool purchases
- Removes free-floating oils to 0.1% or less
- · Prevents rancidity with contiuous overflow
- Purges coalescing media or solids and sludge with automatic air sparger



PRAB GUARDIAN™ COOLANT RECYCLING SYSTEM

EXTENDS TOOL LIFE BY UP TO 25%

Configuration Packages



Base Package

- An inlet basket strainer
- Dirty and clean coolant tanks
- A Tramp Oil Separator with a coalescing media pack
- A floating skimmer assembly
- Steel oil weirs, manifolded together on exterior of the tank
- An automatic air sparging system
- A coolant make-up system


- Control Panel
 - o Allen Bradley components
 - o HMI
- Voltage: 460/3/60
 - o Other voltage options available: contact factory for pricing and lead time



PRAB GUARDIAN™ COOLANT RECYCLING SYSTEM

EXTENDS TOOL LIFE BY UP TO 25%

Configuration Packages Cont.



Standard Package

- An inlet basket strainer
- Dirty and clean coolant tanks
- A Tramp Oil Separator with a coalescing media pack
- A floating skimmer assembly
- Steel oil weirs, manifolded together on exterior of the tank
- An automatic air sparging system
- A coolant make-up system

Additional features included in the Standard Configuration:

- Coolant Manager: Ozone Generator
- Polishing Filter Assembly: typically 20-micron rated filter

- Control Panel
 - o Allen Bradley components
 - o HMI
- Voltage: 460/3/60
 - o Other voltage options available: contact factory for pricing and lead time




Backed by the PRAB Difference

PRAB GUARDIAN™ COOLANT RECYCLING SYSTEM

EXTENDS TOOL LIFE BY UP TO 25%

Configuration Packages Cont.



Deluxe Package

- An inlet basket strainer
- Dirty and clean coolant tanks
- A Tramp Oil Separator with a coalescing media pack
- A floating skimmer assembly
- · Steel oil weirs, manifolded together on exterior of the tank
- An automatic air sparging system
- A coolant make-up system

Additional features included in the Deluxe Configuration:

- Coolant Manager: Ozone Generator
- Polishing Filter Assembly: typically 20-micron rated filter
- Dirty Coolant Transfer System
- Paper Bed Filter: with 10-micron rated filter media
 - o Note: Inlet Basket Strainer has been removed in lieu of the paper bed filter

Control Panel

- o Allen Bradley components
- o HMI
- Voltage: 460/3/60
 - o Other voltage options available: contact factory for pricing and lead time




Backed by the **PRAB Difference**

PRAB GUARDIAN[™] COOLANT RECYCLING SYSTEM REDUCES NEW COOLANT PURCHASES UP TO 75%

Easy to Operate & Maintain

The PRAB Guardian Coolant Recycling System is furnished with an automatic air sparger to maintain clean coalescing media, a high level tramp-oil switch that turns the system off when the tramp-oil container is full, thus eliminating the potential for tramp-oil spillage, and a full control panel for ease of operation. Backed by a 100% Performance Guarantee.

Model	Processing Rate Gallons Per Minute	Dirty/Clean Tank Capacity (Gallons)	Overall Length	Overall Width	Overall Height
HG400	10	200/200	89″	73″	72.5″
HG600	10	300/300	126″	74.5″	76.6″
HG800	15	400/400	154″	76.5″	78.8″
HG1200	15	600/600	168.6″	77.5″	86.1″
HG1600	25	800/800	179.8″	90.3″	94″
HG2000	25	1000/1000	174″	91.3″	101″
HG4000	25	2000/2000	250″	91″	148″



Contact us to request a quote today

5801 East N Avenue, Kalamazoo, MI 49048 Phone: 1-800-968-7722 l Email: sales@prab.com l Website: prab.com



1023-20230522